

## Appendix A

## testMAS : Pressure Sintering

This Process:

[MAS 2.0](#) - [Guides](#) - [F.A.Q.](#) - [Tutorials](#) - [Home](#)

[Basic Info](#)  
[More Info](#)  
[Production](#)  
[Geometry](#)  
[Design Guide](#)  
[Sample Parts](#)  
[Material Use](#)  
[Pros / Cons](#)  
[Variations](#)  
[Theory](#)  
[Links](#)

All Processes:

[Casting-Die](#)  
[Casting-Invest](#)  
[Casting-Sand](#)  
[Casting-Shell](#)  
[Casting-Slip](#)  
[CyberCut](#)  
[EDM](#)  
[Extrusion](#)  
[FDM](#)  
[Forging](#)  
[Forming-Sheet/Metal](#)  
[Inject Metal/Ceramic](#)  
[Inject Plastic](#)  
[JobShopMachining](#)  
[ME3](#)  
[Milling](#)  
[Sintering-Laser](#)  
[Sintering-Pressure](#)  
[Stereolithography](#)  
[Thermoform](#)  
[Transfer Line](#)  
[Turning](#)

Hello

### Basic Information

One process of forming parts of powdered material parts is by compressing the powdered material, metals, or ceramics, in a die and then sintering the piece thus formed. The powder is molded to the required shape, normally at room temperature, by the application of high-tonnage compacting pressure. No binder or adhesive material is used in this operation. Then, the piece is heat-treated by the process known as sintering to induce optimal strength.

Sintering occurs in a controlled-atmosphere furnace where the green piece (piece straight from compaction) is heated to a temperature close to but not at melting. This is done so that particles may bond by solid state bonding, but not melt. Although both non-metallic and metal powders are used in sintering this web page concentrates on powdered metals.

As applied to ferrous powder metallurgy, the sintering process can be defined as *"a method of controlled atmosphere diffusion bonding particles to produce an engineering material."*